



Republic of the Philippines
Benguet State University

2601 La Trinidad, Benguet
www.bsu.edu.ph

Telefax No. (074) 661-1839; Email: procurement@bsu.edu.ph

REQUEST FOR QUOTATION (RFQ)
(ALL ENTRIES ARE MANDATORY)

Name of Owner/ Corporation/ Cooperative/ Agency: _____

QUOTATION NO. 1148

Name of Business : _____

DATE: SEP 09 2024

Address: _____

P.R. NO.: 2024-08-1381

Email address: _____ Telephone No. _____

ABC: 234, 100.00

FUND SOURCE: 161

The Benguet State University through its Bids and Awards Committee will undertake UP - SVP for the item/s listed below under the following terms and conditions:

- All entries must be written legibly and accurately.
- Delivery period is within 30 calendar days.
- Warranty period shall be for a minimum of three months, in case of expendable supplies, and a minimum of one year in case of non- expendable supplies from date of acceptance by the University.
- Price validity shall be for a period of 30 calendar days.
- Compliance with specifications: Kindly specify in the column provided below whether the offer fully complies with the specifications or a counter offer.
- Deadline of submission of quotation is on or before 5:00 PM of Sept. 17, 2024 **Offers may be submitted in sealed or open quotation in person, or through facsimile (074-661-1839) or email (procurement@bsu.edu.ph)**
- The item/s shall be procured by: a) line item; b) lot; c) sub-lot
- Business Permit Number : _____, date of issue: _____, place of issue: _____, (If renewal of Business Permit is still on process, please indicate OR No: _____, date of OR : _____ for the payment of renewal).
- * PhilGEPS Registration Number: _____

SAMUEL S. POLIDEN
Chairperson, BAC (Goods & Services)

College/Dept./Office: ICT

Item No.	Qty	Unit	Item	Technical Specifications (Brand and Model)		ABC	Unit Cost	Total Cost
				COMPLY	COUNTER OFFER			
			IT Equipment and supplies					
1	2	unit	Brand new Layer 3 Smart Switch, 1x 10/100 Ethernet port, 48x 10/100/1000 Ethernet ports, 4 x 10G SFP+ ports, 2 x 40G QSFP+ ports, MIPSBE 32bit Architecture, 650MHz CPU, 98DX3257 switch chip, 64MB RAM, 16MB FLASH storage, RouterOS L5, Passive PoE In, 2x 100-240V AC Input Voltage, 60W Maximum power consumption, 3x cooling fans, Certifications: CE, EAC, & RoHS. Warranty: 1 year.			86,000.00		
2	4	unit	Brand new AX1800 High-performance Outdoor Omni-directional Access Point, Wireless Protocol: 802.11ax (Wi-Fi 6), Throughput: 1775Mbps, MIMO : 2x2 @2.4 GHz, 2x2 @5 GHz, Protection Level : IP68, Power Supply:802.3at PoE, Certifications:CE and ROHS, Network Port:2 x 10/100/1000 Base-T, Max/Recommended Clients : 512/100, Operating Temperature : - 30°C ~ 65 °C, Power Consumption : ≤ 18W, Free Cloud Management, Warranty: 3 years, without PoE Adapter			40,000.00		

3	2	Unit	Brand new Wi-Fi 6 AX3000 High Performance Multi-G Ceiling Access Point, Wireless Protocol: 802.11ax (Wi-Fi 6), 2.97Gbps, Antenna: Built-in Omni-directional, Recommended Clients: 512/110, Power Supply: 802.3at PoE, 12V/2A DC Adaptor, Certifications: CE & ROHS, Network Port: 1 x 100/1000/2500 Base-T and 1 x 10/100/1000 Base-T, MIMO: 2x2 @2.4 GHz, 2x2 @5 GHz, Operating Temperature: 0°C~40°C, Weight: 0.65 kg (excluding mounting kits), Power Consumption: <18 W, Warranty: 3 Years, Free Cloud management, Self Organizing Network, Centralized, Network Management, Remote Monitoring and Maintenance			19,000.00		
4	1	pc	Brand new Mini Optical time-domain reflectometer, 4.3-inch multi-touch capacitive screen, support new gesture, zoom function, screenshot, UPC interface/port, 12-in-1 function, automatic OTDR, expert OTDR, event map, optical power meter, visible red light, adjustable light source, optical loss test, RJ45 network cable to line, RJ45 network cable distance measurement, RJ45 network cable Line hunting, flashlight, end detection, OTDR: 80km 24/22dB, OPM: -70~+10dBm, VFL: 10mw, OTDR/OLS: 1310/15150nm, RJ45 line seeking/sequencing/length function, SC and LC adapters, Support automatic save, SOR file format, 8G storage capacity, can store 200,000 items, Type-C charging interface, 4000mAh polymer battery, battery life is more than 12 hours, Warranty: 1 year			18,000.00		
5	4	pc	Brand new Loaded Optical Distribution Frame (ODF), 12 Fiber Pigtails, Certifications: CE/FC/ROHS/SGS/ISO, 19" Rack Mounted, Drawer and Guide Rails, Cold Rolled Steel/Aluminum Steel, black, Height: 1U, Ports: 12, SC/UPC Connectors, 0.8MM thickness			6,400.00		
6	2	pc	Brand new Loaded Optical Distribution Frame (ODF), Fixed Type, Slidable Type, 24 Fiber Pigtails, Certifications: CE/FC/ROHS/SGS/ISO, 19" Rack Mounted, Drawer and Guide Rails, Cold Rolled Steel/Aluminum Steel, black, Height: 1U, Ports: 24, SC/UPC Connectors, 0.8MM thickness			4,000.00		
7	12	pc	Brand new 4 core Fiber Optic Distribution Box FTTH, IP65, ABS+PC Material, Dimensions: 186X116X41mm (W x H x D)			3,600.00		
8	4	pack	Brand new 10-piece pack Open Tail Fiber Optic Fast Linker, Connector Type: Quick Connector, SC/UPC, Insertion loss: ≤0.3dB (Max0.5), Return Loss: ≥50dB, Variation: ≤0.2db, Rally: ≥35N, Torque: ≥25N, Repeat assembly: ≥15 times, Size: 60x8.9mmx7mm/2.36x0.35", Ferrule Material: Plastic, Item Diameter: 200.00mm, Applicable optical fiber: 2.0*3.0 butterfly optical cable, Working temperature: -40°C~+70°C, Relative Humidity (Rh): 168%			600.00		
9	1	pack	New Fiber Pigtail 100 PCS LC UPC Optic Fiber LC Patch Cord Single Mode 9/125 μm 0.9mm 1M			9,000.00		
10	1	pack	New Fiber Pigtail 100 PCS LC UPC Optic Fiber LC Patch Cord Multi Mode 50/125μm 0.9mm 1M OM2			9,800.00		
11	30	pc	Single Mode Duplex Fiber Optic Patch Cable 9/125 LC to LC UPC			10,500.00		
12	30	pc	LC-LC Multimode Duplex 3.0mm10GBPS OM3 Fiber Patch Cable Cord 3 meters			9,000.00		
13	10	pc	Brand new Data Cabinet Fan, Material: Metal, Color: Black, Size: 120x120x38mm/4.72x4.72x1.50in (Approx.), Fan Diameter: 120mm/4.72" (Approx.), Bearing Type: Sleeve, Voltage: AC 220-240V, Rated Current: 0.14A, Power: 23/21 (W), Frequency: 50/60 (Hz), Power Connection: 2-Wire, Speed: 2500RPM ±10%, Airflow: 75CFM ±10%, Noise: 38dBA±10%			2,200.00		

