



Republic of the Philippines
Benguet State University

2601 La Trinidad, Benguet
www.bsu.edu.ph
Telefax No. (074) 661-1839; Email:procurement@bsu.edu.ph



REQUEST FOR QUOTATION (RFQ)
(ALL ENTRIES ARE MANDATORY)

Name of Business : _____
Address: _____
Email address: _____ Telephone No. _____

QUOTATION NO. 1090
DATE: SEP 02 2024
P.R. NO. : 2024-06-1036
ABC: Php. 170,000.00
FUND SOURCE: SP

The Benguet State University through its Bids and Awards Committee will undertake NA 51P for the item/s listed below under the following terms and conditions:

- All entries must be written legibly and accurately.
- Delivery period is within 15 calendar days.
- Warranty period shall be for a minimum of three months, in case of expendable supplies, and a minimum of one year in case of non- expendable supplies from date of acceptance by the University.
- Price validity shall be for a period of 30 calendar days.
- Compliance with specifications: Kindly specify in the column provided below whether the offer fully complies with the specifications or a counter offer.
- Deadline of submission of quotation is on or before 5:00 PM of Sept. 9, 2024. Offers may be submitted in sealed or open quotation in person, or through facsimile (074-661-1839) or email (procurement@bsu.edu.ph)
- The item/s shall be procured by: _____ a) line item; _____ b) lot; _____ c) sub-lot
- Business Permit Number : _____, date of issue: _____, place of issue: _____, (If renewal of Business Permit is still on process, please indicate OR No: _____, date of OR : _____ for the payment of renewal).
- * PhilGEPS Registration Number: _____

SAMUEL S. POLIDEN
Chairperson, BAC (Goods & Services)

College/Dept./Office: **CorCAARRD**

Item No.	Qty	Unit	Item	Technical Specifications (Brand and Model)		ABC	Unit Cost	Total Cost
				COMPLY	COUNTER OFFER			
			Supply and delivery of Audio System Breakdown:					
			1) Active Speakers (4 Pcs) Rugged plastic mold design cabinet, bottom pole mount for tripod stand, signal loop for extended system application, USB/Bluetooth, Line level and direct mic guitar input, DSP management control w/ atleast 5 preset settings, 2 Way Bass Reflex, min of 10" Woofer (at least 2" Voice coil size), titanium Dome Tweeter, 48Hz-20KHz freq response, Power@ 300W min., Input Impedance: 20K ohms, Input Gain: line: +20 dBu /Mic: +40dB, Line (RCA & XLR) / Mic (PL&XLR) input connector, Output Connector: Line (XLR loop through), LED Indicator for Power, Signal, Clip, Crossover Frequency: 2.5KHz, 220V 50-60Hz AC input, with OEM tripod					
			2) Mixer: (1 pc) 12 Channel Compact Mixer, 8 Mic/line 2 Stereo Input, 3 Band EQ, 24 bit 99 DSP Digital Effect, Mute and Solo Function, Phantom Power 48V, 2 BUS headphone and Foot Switch, 2 Aux out, USB/Mp3 Function, Bluetooth					
			3) Graphic Equalizer (1 pc) Dual 15 Band 2/3 Octave Constant, Balance XLR and TRS Connector, +/- 12 dB Input Gain, 18 dB/ Octave, 40 hz Bessel Low Cut Filter					

1	1	Lot	4) Wired Microphone (2 pcs) Cardioid Precision Dynamic Wired with 38mm Large Diaphragm, Magnetic Switch, Uniform pick-up patter for maximum gain before feedback, Tailored frequency response for vocals, Rubber shock mount system that minimizes transmission of mechanical noise and vibration, Built-In foam-filter on steel-mesh grille, reduces undesirable wind noise, On/Off switch, Durable and reliable under the heaviest use, 10 meters cord					
			5) DriveRack Complete Loudspeaker Management System (1 pc) 2 line inputs 1 RTA Mic inputs, Input Connectors (2) Female XLR line inputs (1) Female XLR RTA Mic input, Input Type - Electronically balanced/RF filtered, Input Impedance >50 kohm, A/D Converter Conversion System, CMRR > 45dB, Mic Preamp Phantom Power +15VDC (RTA), Mic Preamp Equivalent Input Noise (EIN), 6 Line Outputs, Output Connectors Male XLR, Output Type - Electronically balanced & RF filtered, Output Impedance 120 Ω, Max Output +20dBu, A/D Dynamic Range - 112 dB A-weighted, 110 dB unweighted, Type IV Dynamic Range - 123 dB with transient material, A-weighted, 22kHz, BW; 121 dB with transient material, unweighted, 22kHz BW; 115 dB typical with program material, A-weighted, 22kHz BW, Input Delay Length - 100ms, Alignment Delay 10 ms per channel (60ms total), Sample Rate - 48kHz, Dynamic Range - >110 dB A-weighted, >107dB unweighted, THD+Noise - 0.003% typical at +4dBu, 1kHz, 0dB input gain, Interchannel Crosstalk < -110 dB, -120dB typical (input-to-output: < -100 dB), Operating Voltage 100-120VAC 50/60 Hz - EU: 220-240 VAC 50/60 Hz (all items are of minimum requirements)					
			6) Flight Case Power Amplifier Rack (1 pc): 12U rack space, 56CM Deep min. (excluding lids), Compressed polyethylene shock absorbing foam, 9mm plywood construction with PVC exterior, Aluminum-reinforced plywood and metal corners, Heavy duty twist latches, rubber-gripped handles and top-quality casters, industrial-grade latches and casters, 11U top space					
			7) Rack Mount Power Sequence Controller Conditioner Surge Protector Power Supply (1 pc), with individual switch, at least 10-outlet , 1U					
			8) AVR Automatic Voltage Regulator (1 pc) 3000VA or higher, Universal Sockets @220V/110V, Short Circuit Protection, Overload Protection, Time Delay Function , Servo Motor Control System, Analog Volt Meter, Ammeter, Protective Overloading current (input)					
			9) Wireless Microphone System (1 set): 4 UHF wireless microphones, Frequency range: 630-690 MHz, 200 selectable frequencies, 50 freq each channel, autofrequency search, LCD display on transmitter and receiver, iU space rack mountable, 4 antenna, Dedicated lithium battery 3.71v/1100mah (min)					
			10) Cables (lot) 1. Audio cables set to connect all devices (connectors, speaker wires at 20 meters with terminators for each speaker, power cables (AVR to speakers) 2. 3.5 to 2RCA audio cable, heavy duty, 3 meters, gold plated, PVC outer cover material, strong and durable, 3 pcs					
			11) Battery charger (1 set) For 1.2V AA, AAA, NiMH or Hydride and NiCd rechargeable battery types, Fast charging, independent charging channel, support mixed charge and quick release, LCD screen smart display charging and discharging process, with atleast 12 charging slots, with AC-DC adapter, comes with free 20 pcs AA Ni-MH 3000Ma minimum rechargeable batteries					
						TOTAL	170,000.00	

Counter offers:

Delivery Period: _____

Warranty: _____

Price Validity: _____

We hereby submit our quotations, accept the general conditions for the above items and be bound by our offer.

Signature over Printed Name

Date and Time of Receipt of RFQ

* Not a ground for disqualification for failure to indicate but required as a condition for award.

Revised: 9/19/2022

282 RFQ 1090