



Republic of the Philippines
BENGUET STATE UNIVERSITY
 La Trinidad, Benguet

PURCHASE ORDER

Supplier: **L&L Laboratory Supplies** P.O. No.: **104 - 0 - 244 - 267**
 Address: **San Antonio Ave., Parangarigan City, Manila** Date: **10/01/2024**
 Title: _____ Mode of Procurement: **P/P - S/P**
 PR No.: **2024-38**

Sir/Madam: please furnish this Office the following articles subject to the terms and conditions contained herein:
 Delivery Term: **FOB Destination**
 Place of Delivery: **BSU SP/MO**
 Date of Delivery: **within 60 calendar days upon acceptance of PO**
 Payment Term: **within 30 days after complete delivery**

Item No.	Particular	Quantity	Unit Cost	Amount	END USER
2	<p>Electric Microscope (Brand: Gaeulnook) Trinocular Compound (Research-Grade) microscope 40x-2000X magnification with HD Recording monitor 27" and AVR Microscope's Specifications: Eyepieces: Pair of WF (width) 10X and 25X, objectives: Plan Achromatic Objective lens DIN 4x, 10x,40x(03), 100x(S oil) Head: 360-degree rotation capability; Mechanical Stage: 3-D double slide; Size: 4.50x5" (115mmx127mm); Travel range: (X-Y), 2-13/16" (70mmx10mm) Condenser: Brightfield, LED illumination with shut-off to control light intensity, and Kohler condenser with two iris diaphragms and for precise focus, clear examination, and light control. GS and CE approved Focusing: coarse & fine knobs on both sides power supply: 100-240VAC, 50/60Hz AODC adapter included Dimension: 11.57" x 18.34" (293mmx178mm)50mm Monitor Specifications: Monitor: ABS, DATA format, 4FAG2AV1 Image sensor: 2MP High quality image sensor Display: 9 inches 16 point, 16:9 Resolution: 1920*1080, 120Hz/90, 840*480 Operation system: Windows XP, Vista, Win7/8/10, Max: 10.5 or above. Interface: USB 2.0, Power Squeeze Rated voltage: AC 110-240V</p> <p>Packing list: 1* storage carrying Hard Bag 1* CF1001 Trinocular compound Microscope 1* 6pcs prepared slide 1* 2.0mp 9 inches monitor 1 Plan Achromatic objective lens, 4x10x(03)100x(S oil) 1* 6cell cell (3m), 1*10K 2*25X eyepiece 1* 6cell cord, 1* 2mp monitor, 1* adapter, 1* power wire 1* USB port connect cable, 1* CD with software Hot Air Sterilizer Forced Air Drying Oven with AVR Specification: Brand: Faimat, Model: WGL-2308 Cycle table: Forced convection, Temp Range: RT+10-300°C, Temp. Resolution: 0.1°C Temp. Median: +1°C, Temp. Uniformity: +2.5%, Inner Chamber: Mirror Stainless Steel Outer Shell: Cold rolling steel electrostatic spray-painted, insulation layer, High quality rock wool board</p>	1	82,667.00	82,667.00	Theresa P. CVM
6	<p>Hot Air Sterilizer Specification: Brand: Faimat, Model: WGL-2308 Cycle table: Forced convection, Temp Range: RT+10-300°C, Temp. Resolution: 0.1°C Temp. Median: +1°C, Temp. Uniformity: +2.5%, Inner Chamber: Mirror Stainless Steel Outer Shell: Cold rolling steel electrostatic spray-painted, insulation layer, High quality rock wool board</p>	1	115,161.00	115,161.00	

MO - GMA-363

	<p>(with CE). Heater: Stainless steel heater. : Power Rating: 3.0KW. Exhaust: Inlet; Rear Exhaust Temp. control mode: Touch bottom sensing Temp. display mode: B model measuring temperature. Display on the flow digital tube upper row, sensing temperature; display on the lower row. Timer: 0-99999999min (timing with function) operation function; fixed temperature operation; timing operation function; auto stop. Additional function: B model, Sensor Dynation, Corrosion temperature overshoot self-tuning thermal parameter locking power off parameter memory. Sensor: Pt100 Inner chamber size: (W*L*H)(mm): 500*500*750 Exterior size: (W*L*H)(mm): 735*835*1115 Packing size: (W*L*H)(mm): 535*825*1287 Volume: 200L, Max. Shelf number: 17, Load per rack: 15kg shelf spikes: 40mm, Power rating: 5000W-20AC/220V/13 BA W/MSHP30; 94/120, Accessory: Shelf: 2 shelf frame: 4 Hemacell centrifuge with AVR features: Strong plastic case with initial 1st High power brushless motor Lead display speed and timer; microcomputer, controlling Overload and emergency alarm with mechanical door lock and safety switch Error code display, speed up and down adjustment with brake and automatic alarm after operation with master Accuracy measuring the specific value of blood cell Separating micro-amount of blood or solution specifications BRAND: FANTHELU, Model: FHC-120 MAX RPM: 12000RPM MAX RCF: 18300g, Timer: 0-99min, Rotol capacity: 01.875mm*24 capillary tube, Voltage: 110V 50HZ/220V 50HZ Dimension: 280*310*265mm; Weight: 10kg</p>	<p>1 83,604.00 83,604.00</p>
<p>7</p>	<p>unit</p>	<p>281,432.00</p>

Total Amount in Words: Two hundred eighty one thousand four hundred thirty two pesos.
 In case of failure to make the full delivery within time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.

Conforme: CAMELIA CASUELA
 Signature over-Printed Name of Supplier
10-26-2024
 Date

Very truly yours,

 CAMELIA CASUELA
 University President

Fund _____
 Cluster: _____
 Funds Available: _____

ISELDA GONZALEZ
 ACCOUNTANT
 Accountant

ORS/BURS No.: 2024-10-2701
 Date of the ORS/BURS: 10/27/2024
281,432